

Modelo / Model / Modelo	MTAC-12,0 JO4-75 (20)									
										
Umáx. / Um / Umax. (kV)	12,0									
Tensão Sup. / Pow. Freq. Volt. / Ens. Dielec. (kV)	38									
NBI / BIL / BIL (kV)	75									
Dist. Escoa. / Creep. Distan. / Dist. Fuga (mm)	166									
Nº Saias / Nº Rippes / Nº Saias	4									
Peso / Weight / Peso (kg)	0,410									
Temp. Trab. / Work Temp. / Temp. Trab. (°C)	-20 até/ up to / hasta +75°C									
Cor / Color / Cor	Marrom/Brown/Marrón RAL 8016									
Flexão / Bending / Flexion (N)	> 4000 (P ₀)									
Capacitância / Capac. / Capac. (pF)	20									
Insertos / Inserts / Insertos IEC 273 → DIN 48136 →	D1	C1 (mm)	T1 (N.m)	D2	C2 (mm)	T2 (N.m)	D3	C3 (mm)	T3 (N.m)	
	M12	18	39	M12	18	39	-	-	-	
	1/2"	18	39	1/2"	18	39	-	-	-	
	M12	18	39	M16	33	147	-	-	-	
	1/2"	18	39	5/8"	33	147	-	-	-	
	M10	16	34	M16	33	147	M6	12	7,8	
Dimensões / Dimensions / Dimensiones (mm)										