


Modelo / Model / Modelo

MTAC-24,0 JO4-125 (150)



Umáx. / Um / Umax.

(kV)

24,0

Tensão Sup. / Pow. Freq. Volt. / Ens. Dielec.

(kV)

50

NBI / BIL / BIL

(kV)

125

Dist. Escoa. / Creep. Distan. / Dist. Fuga

(mm)

293

Nº Saias / Nº Ripples / Nº Saias

8

Peso / Weight / Peso

(kg)

1,130

Temp. Trab. / Work Temp. / Temp. Trab.

(°C)

-20 até/ up to / hasta +75°C

Cor / Color / Cor

Marron/Brown/Marrón RAL 8016

Flexão / Bending / Flexion

(N)

> 4000 (P₀)

Capacitância / Capac. / Capac.

(pF)

150

Insertos / Inserts / Insertos

	D1	C1	T1	D2	C2	T2	D3	C3	T3
		(mm)	(N.m)		(mm)	(N.m)	(x2)	(mm)	(N.m)
	M12	18	39	M12	18	39	-	-	-
	1/2"	18	39	1/2"	18	39	-	-	-
IEC 273 →	M12	18	39	M16	33	147	-	-	-
	1/2"	18	39	5/8"	33	147	-	-	-
DIN 48136 →	M10	16	34	M16	33	147	M6	12	7,8

Dimensões / Dimensions / Dimensiones

(mm)

