


Modelo / Model / Modelo

MTA-05,0 JO4-60



Umáx. / Um / Umax. (kV)	5,0
Tensão Sup. / Pow. Freq. Volt. / Ens. Dielec. (kV)	28
NBI / BIL / BIL (kV)	60
Dist. Escoa. / Creep. Distan. / Dist. Fuga (mm)	130
Nº Saias / Nº Ripas / Nº Saias	2
Massa / Mass / Masa (kg)	0,410
Temp. Trab. / Work Temp. / Temp. Trab. (°C)	-20 até/ up to / hasta +75°C
Cor / Color / Cor	Marrom/Brown/Marrón RAL 8016
Flexão / Bending / Flexion (N)	> 4000 (P ₀)

Insertos / Inserts / Insertos IEC 60273 →	D1	C1	T1	D2	C2	T2	D3	C3	T3
		(mm)	(N.m)		(mm)	(N.m)	(x2)	(mm)	(N.m)
	M12	18	25	M12	18	25	-	-	-
	1/2"	18	25	1/2"	18	25	-	-	-
	M12	18	25	M16	33	75	-	-	-
	1/2"	18	25	5/8"	33	75	-	-	-
	M10	16	20	M16	33	75	M6	12	6

Dimensões / Dimensions / Dimensiones (mm)

